



Superior Clamping and Gripping



## Product Information

Universal gripper PGN-plus 240

## Reliable. Robust. Flexible.

### Universal gripper PGN-plus

Universal 2-finger parallel gripper with a high gripping force and high maximum moments due to the use of a multi-tooth guidance

#### Field of application

Optimal standard solution for many fields of application. For universal use in clean to slightly dirty environments. Special versions available for dirty environments.

#### Advantages – Your benefits

**Robust multi-tooth guidance** for precise handling

**High maximum moments possible** suitable for using long gripper fingers

**Drive concept oval piston** for maximum gripping forces

**Mounting from two sides in three screw directions** for universal and flexible gripper assembly

**Air supply via hose-free direct connection or screw connections** for universal and flexible gripper assembly

**Comprehensive sensor accessory program** for versatile querying possibilities and stroke position monitoring

**Compact dimensions** for minimal interfering contours in handling

**Manifold options** for special optimization for your specific case of application (dustproof, high-temperature, corrosion-protected, etc.)



Sizes  
Quantity: 11



Weight  
0.08 .. 39.5 kg



Gripping force  
123 .. 21150 N




Stroke per jaw  
2 .. 45 mm



Workpiece weight  
0.62 .. 80.5 kg

## Functional description

The oval piston is moved up or down by compressed air. The angled active surfaces of the wedge-hook produce a synchronized, parallel jaw motion.



- ① **Multi-tooth guidance**  
highly loadable, nearly backlash-free base jaw guidance for long finger lengths
- ② **Base Jaw**  
for the connection of workpiece-specific gripper fingers
- ③ **Sensor system**  
Brackets for proximity switches and adjustable control cams in the housing

- ④ **Housing**  
is weight-optimized due to the use of high-strength aluminum alloy
- ⑤ **Centering and mounting possibilities**  
for universal assembly of the gripper
- ⑥ **Wedge-hook design**  
for high force transmission and centric gripping

## General notes about the series

**Operating principle:** Wedge gear with surface power transmission

**Housing material:** Aluminum

**Base jaw material:** Steel

**Actuation:** pneumatic, with filtered compressed air as per ISO 8573-1:2010 [7:4:4].

**Warranty:** 36 months

**Scope of delivery:** Brackets for proximity switches, centering sleeves, O-rings for direct connection, assembly instructions (operating manual with declaration of incorporation is available online)

**Gripping force maintenance device:** possible by using the version with mechanical gripping force maintenance or pressure maintenance valve SDV-P

**Gripping force:** is the arithmetic sum of the individual force applied to each jaw at distance P (see illustration).

**Finger length:** is measured from the reference surface as the distance P in direction to the main axis.


The maximum permissible finger length applies until the nominal operating pressure is achieved. With higher pressures, the finger length must be reduced proportionally to the nominal operating pressure.

**Repeat accuracy:** is defined as a distribution of the end Position for 100 consecutive strokes.

**Workpiece weight:** is calculated for force-fit gripping with a coefficient of static friction of 0.1 and a safety factor of 2 against workpiece slippage at acceleration due to gravity g. For form-fit or capture gripping, there are significantly higher permissible workpiece weights.

**Closing and opening times:** are purely the times that the base jaws or fingers are in motion. Valve switching times, hose fill times, or PLC reaction times are not included, and are to be considered when cycle times are calculated.

**Cleanroom class ISO 14644-1:** 5



## Application example

Handling gantry with multiple grippers for simultaneous removal of several workpieces

① 2-finger parallel gripper PGN-plus


② Linear module CLM

③ Universal linear module LDN

④ Universal linear module Beta

## SCHUNK offers more ...

The following components make the product even more productive – the suitable addition for the highest functionality, flexibility, reliability, and controlled production.



Linear module



Quick change system



Universal swivel unit



Compensation unit



Jaw quick-change system



Universal intermediate jaw



Pressure maintenance valve



Manual change system



Finger blank



Flexible position sensor



Magnetic switches



Inductive proximity switches

① For more information on these products can be found on the following product pages or at [schunk.com](http://schunk.com).

## Options and special information

**Gripping force maintenance version AS/IS:** The mechanical gripping force maintenance version ensures minimum gripping force even in the event of a pressure drop. In the AS/S version this acts as a closing force, in the IS version as an opening force.

**Anti-corrosion version K:** for use in corrosion-inducing atmospheres

**High-temperature version V/HT:** for use in hot environments

**Power booster version KVZ:** if higher gripping forces are required

**Precision version P:** for the highest accuracy


**ATEX version EX:** for explosive environments

**Dustproof version SD:** absolutely dustproof, increased degree of protection against ingress of materials.

**Additional versions:** Various options can be combined with each other.

## SCHUNK gripper PGN-plus

### Overview Accessories





- 1 **PGN-plus**  
Universal 2-finger parallel gripper with a high gripping force and high maximum moments due to the use of a multi-tooth guidance

### Sensor system

- 2 **IN ...**  
Inductive proximity switch with molded cable and straight cable outlet
- 3 **IN ...-SA**  
Inductive proximity switch with molded cable and lateral cable outlet
- 4 **IN-C 80**  
Inductive proximity switch, directly pluggable
- 5 **FPS**  
Flexible position sensor for monitoring up to five different, freely selectable positions
- 6 **APS-Z80**  
Inductive position sensor for precise position detection of the gripper jaws with analog output
- 7 **APS-M15**  
Mechanical measuring system for precise position detection of the gripper jaw with analog output
- 8 **RMS 80**  
Reed switch in round version
- 9 **MMS 22**  
Magnetic switch with straight cable outlet for monitoring a position  
  
**MMS 22-PI1**  
Magnetic switch with straight cable outlet for monitoring a freely programmable position
- 10 **MMS 22-PI2**  
Magnetic switch with straight cable outlet for monitoring two freely programmable positions
- 11 **MMS 22-PI1-HD**  
MMS 22-PI1 in robust design  
  
**MMS 22-PI2-HD**  
MMS 22-PI2 in robust design
- 12 **MMS 22-SA**  
Magnetic switch with lateral cable outlet for monitoring a position  
  
**MMS 22-PI1-SA**  
Magnetic switch with side cable outlet for monitoring a freely programmable position
- 13 **MMS-P**  
Magnetic switch with straight cable outlet for monitoring two freely programmable positions
- 14 **MMS 22-A**  
Analog magnetic switch with straight cable outlet for measuring the gripper jaw position with analog output and teach function

- 15 **RMS 22**  
Reed switch for direct assembly in the C-slot

### Complementary products


- 16 **CWS**  
Manual change system with integrated air feed-through for simple exchange of the handling components
- 17 **TCU**  
Tolerance compensation unit for compensating small tolerances in the plane
- 18 **SDV-P-E-P**  
Pressure maintenance valve for temporary force and position maintenance
- 19 **AGE**  
Compensation unit for compensation of large tolerances along the X and Y axes
- 20 **ASG**  
Adapter plate for combining various automation components in the modular system
- 21 **CLM**  
Linear module with pneumatic drive and scope-free pre-loaded junction rollers
- 22 **HUE**  
Sleeve for protection against dirt

### Finger Accessories


- 23 **UZB**  
The universal intermediate jaw allows fast tool-free and reliable plugging and shifting of top jaws at the gripper.
- 24 **BSWS-AR**  
Adapter coupling of jaw quick-change system for fast, manual change of top jaws
- 25 **BSWS-B**  
Locking mechanism of the jaw quick-change system for fast, manual exchange of top jaws
- 26 **BSWS-A**  
Adapter coupling of the jaw quick-change system for adaptation to the customized finger
- 27 **Customized fingers**
- 28 **BSWS-ABR**  
Finger blank made of aluminum with interface to the jaw quick-change system  
  
**BSWS-SBR**  
Finger blank made of steel with interface to the jaw quick-change system
- 29 **BSWS-UR**  
Locking mechanism for the integration of the jaw quick-change system into customized fingers
- 30 **ABR/SBR**  
Finger blanks made of steel or aluminum with standardized screw connection diagram
- 31 **ZBA**  
Intermediate jaws for reorientation of the mounting surface

# PGN-plus 240


Universal gripper




## Gripping force O.D. gripping



## Gripping force I.D. gripping



## Dimensions and maximum loads



① The indicated moments and forces are static values, apply for each base jaw and may appear simultaneously. Loads may additionally occur to the moment produced by the gripping force itself.

## Technical data

Description		PGN-plus 240-1	PGN-plus 240-2	PGN-plus 240-1-AS	PGN-plus 240-2-AS	PGN-plus 240-1-IS	PGN-plus 240-2-IS
ID		0371108	0371158	0371408	0371458	0371468	0371478
Stroke per jaw	[mm]	30	17	30	17	30	17
Closing/opening force	[N]	4200/4440	6500/6870	5300/-	8340/-	-/5540	-/8710
Min. spring force	[N]			1100	1840	1100	1840
Weight	[kg]	8.5	8.5	12	12	12	12
Recommended workpiece weight	[kg]	21.5	33	21.5	33	21.5	33
Fluid consumption double stroke	[cm³]	650	650	810	810	995	995
Min./nom./max. operating pressure	[bar]	2.5/6/8	2.5/6/8	4/6/6.5	4/6/6.5	4/6/6.5	4/6/6.5
Min./max. air purge pressure	[bar]	0.5/1	0.5/1	0.5/1	0.5/1	0.5/1	0.5/1
Closing/opening time	[s]	0.45/0.45	0.45/0.45	0.35/0.65	0.35/0.65	0.65/0.35	0.65/0.35
Closing/opening time with spring	[s]			0.55	0.55	0.55	0.55
Max. permissible finger length	[mm]	320	280	280	240	280	240
Max. permissible mass per finger	[kg]	8.5	8.5	8.5	8.5	8.5	8.5
IP protection class		40	40	40	40	40	40
Min./max. ambient temperature	[°C]	5/90	5/90	5/90	5/90	5/90	5/90
Repeat accuracy	[mm]	0.04	0.04	0.04	0.04	0.04	0.04
Dimensions X x Y x Z	[mm]	270 x 115 x 107	270 x 115 x 107	270 x 115 x 163.5	270 x 115 x 163.5	270 x 115 x 163.5	270 x 115 x 163.5
<b>Options and their characteristics</b>							
Dustproof version		37371108	37371158	37371408	37371458	37371468	37371478
IP protection class		64	64	64	64	64	64
Weight	[kg]	9.1	9.1	12.6	12.6	12.6	12.6
Corrosion-protected version		38371108	38371158	38371408	38371458	38371468	38371478
High-temperature version		39371108	39371158	39371408	39371458	39371468	39371478
Min./max. ambient temperature	[°C]	5/130	5/130	5/130	5/130	5/130	5/130
Precision version		0371128	0371178	0371428	0371443		

① It may take a few 100 gripping cycles until the full gripping force (as indicated in the data table) will be available.




- ② Finger connection
- 72 Fit for centering sleeves
- 80 Depth of the centering sleeve hole in the counter part
- 90 Sensor MMS 22..
- 91 Sensor IN ...





## BSWS jaw quick-change jaw systems



⑨0 SDV-P pressure maintenance valve

⑨ Customized gripper fingers

Description	ID	Recommended hose diameter
		[mm]
Pressure maintenance valve		
SDV-P 07	0403131	8
Pressure maintenance valve with air bleed screw		
SDV-P 07-E	0300121	8
SDV-P 10-E	0300109	10

- | Description                         | ID      | Scope of delivery |
|-------------------------------------|---------|-------------------|
| Quick-change jaw system base        |         |                   |
| BSWS-B 240                          | 0303035 | 1                 |
| Jaw quick-change system adapter pin |         |                   |
| BSWS-A 240                          | 0303034 | 2                 |

- ### Fields of application

Series	Size	Variant	Suitability
PGN-plus	240	-1 (6 bar)	■■■■
PGN-plus	240	-1-AS / -1-IS (6 bar)	■■■■
PGN-plus	240	-2 (6 bar)	■■■■
PGN-plus	240	-2-AS / -2-IS (6 bar)	■■■■
<b>Legend</b>			
■■■■		Can be combined without restrictions	
■■□□		Use with restrictions (see loading limits)	
□□□□		cannot be combined	


The load limits for describing the application limits can be found in the catalog chapter of the corresponding accessories.

If the operating pressure is higher than 6 bar, suitability for use above the application limits must be checked.

# PGN-plus 240

Universal gripper

## ZBA-L-plus 240 intermediate jaws




- ② Finger connection
- ⑤6 Included in the scope of delivery
- ⑦2 Fit for centering sleeves
- ⑧0 Depth of the centering sleeve hole in the counter part
- ⑧1 Not included in the scope of delivery

The optional ZBA-L-plus intermediate jaws allow the screw connection diagram of the top jaws to be rotated by 90°. This makes it easier to design and produce top jaws (particularly for long versions) because no deep through-bores are required.

Description	ID	Material	Finger interface	Scope of delivery
Intermediate jaw				
ZBA-L-plus 240	0311782	Aluminum	PGN-plus 240	1

## Finger blanks ABR- / SBR-PGZN-plus 240




- ② Finger connection
- ⑦2 Fit for centering sleeves

The drawing shows the finger blank which can be reworked by the customer.

Description	ID	Material	Scope of delivery
Finger blank			
ABR-PGZN-plus 240	0300017	Aluminum	1
SBR-PGZN-plus 240	0300027	Steel	1

## Tolerance compensation unit TCU




- ⑨0 Monitoring of locking

Grippers can be directly mounted without an adapter plate. Tolerance compensation unit and gripper have an identical screw connection diagram. Therefore the tolerance compensation units can be assembled later. Please consider the additional assembly height of the tolerance compensation unit. For details please refer to our catalog robot accessories.

Description	ID	Locking	Deflection	Often combined
Compensation unit				
TCU-P-240-3-MV	0324730	yes	±1°/±1,5°/±1°	●
TCU-P-240-3-OV	0324731	no	±1°/±1,5°/±1°	

## Inductive Proximity Switches




- ① Cable outlet                      ⑨ Sensor IN...-SA  
 ⑨ Sensor IN ...

Directly mounted end position monitoring.

Description	ID	Often combined
Inductive proximity switches		
IN 80-S-M12	0301578	
IN 80-S-M8	0301478	●
INK 80-S	0301550	
Inductive proximity switch with lateral cable outlet		
IN 80-S-M12-SA	0301587	
IN 80-S-M8-SA	0301483	●
INK 80-S-SA	0301566	
Connection cables		
KA BG08-L 3P-0300-PNP	0301622	●
KA BG08-L 3P-0500-PNP	0301623	
KA BG12-L 3P-0500-PNP	30016369	
KA BW08-L 3P-0300-PNP	0301594	
KA BW08-L 3P-0500-PNP	0301502	
KA BW12-L 3P-0300-PNP	0301503	
KA BW12-L 3P-0500-PNP	0301507	
clip for plug/socket		
CLI-M12	0301464	
CLI-M8	0301463	
Cable extension		
KV BG12-SG12 3P-0030-PNP	0301999	
KV BG12-SG12 3P-0060-PNP	0301998	
KV BW08-SG08 3P-0030-PNP	0301495	
KV BW08-SG08 3P-0100-PNP	0301496	
KV BW08-SG08 3P-0200-PNP	0301497	●
KV BW12-SG12 3P-0030-PNP	0301595	
KV BW12-SG12 3P-0100-PNP	0301596	
KV BW12-SG12 3P-0200-PNP	0301597	
Sensor distributor		
V2-M12	0301776	●
V2-M8	0301775	●
V4-M8	0301746	
V8-M8	0301751	

- ① Two sensors are required per unit for monitoring two positions. On option, extension cables and sensor distributors are available. Additional product variants of the sensor, and further information and technical data can be found in the catalog chapter sensor system.

Flexible position sensor




- 90 FPS-S sensor
- 91 FPS-F5 evaluation electronic
- 92 Cable extension

Flexible position monitoring of up to five positions.

Description	ID	
Attachment kit for FPS		
AS-FPS-PGZN-plus 240-1	0301643	
AS-FPS-PGZN-plus 240-2	0301644	
Sensor		
FPS-S M8	0301704	
Evaluation electronics		
FPS-F5	0301805	
Cable extension		
KV BG08-SG08 3P-0050	0301598	
KV BG08-SG08 3P-0100	0301599	

- ① When using an FPS system, an FPS sensor (FPS-S) as well as an electronic processor (FPS-F5 / F5 T) are required for each gripper as well as a mounting kit (AS), if listed. Cable extensions (KV) are optionally available – see catalog chapter "Accessories."

Electronic magnetic switch MMS



- 17 Cable outlet
- 90 Sensor MMS 22..
- 91 Sensor MMS 22...-SA


End position monitoring for mounting in the C-slot.

Description	ID	Often combined
Electronic magnetic switch		
MMS 22-S-M8-PNP	0301032	●
MMSK 22-S-PNP	0301034	
Electronic magnetic switches with lateral cable outlet		
MMS 22-S-M8-PNP-SA	0301042	●
MMSK 22-S-PNP-SA	0301044	
Reed Switches		
RMS 22-S-M8	0377720	●
Connection cables		
KA BG08-L 3P-0300-PNP	0301622	●
KA BG08-L 3P-0500-PNP	0301623	
KA BW08-L 3P-0300-PNP	0301594	
KA BW08-L 3P-0500-PNP	0301502	
clip for plug/socket		
CLI-M8	0301463	
Wireless sensor system		
RSS-T2	0377715	
RSS-T2-US/CA	0377717	
Cable extension		
KV BW08-SG08 3P-0030-PNP	0301495	
KV BW08-SG08 3P-0100-PNP	0301496	
KV BW08-SG08 3P-0200-PNP	0301497	●
Sensor distributor		
V2-M8	0301775	●
V4-M8	0301746	
V8-M8	0301751	

- ① Two sensors are required per unit for monitoring two positions. On option, extension cables and sensor distributors are available. Additional product variants of the sensor, and further information and technical data can be found in the catalog chapter sensor system.



## Programmable magnetic switch MMS 22-PI1




- ①⑦ Cable outlet                      ①⑨ Sensor MMS 22 ..-PI1-...-SA  
①⑩ Sensor MMS 22 PI1-...

Position monitoring with one programmable position per sensor and integrated electronic system in the sensor. Can be programmed using MT magnetic teaching tool (included in the scope of delivery) or ST plug teaching tool (optional). End position monitoring for mounting in the C-slot. If the ST plug teaching tools are listed in the table provided, teaching is only possible with the ST teaching tools.

Description	ID	Often combined
<b>Programmable magnetic switch</b>		
MMS 22-PI1-S-M8-PNP	0301160	●
MMSK 22-PI1-S-PNP	0301162	
<b>Programmable magnetic switch with lateral cable outlet</b>		
MMS 22-PI1-S-M8-PNP-SA	0301166	●
MMSK 22-PI1-S-PNP-SA	0301168	
<b>Programmable magnetic switch with stainless steel housing</b>		
MMS 22-PI1-S-M8-PNP-HD	0301110	●
MMSK 22-PI1-S-PNP-HD	0301112	

- ① Two sensors are required per unit for monitoring two positions. On option, extension cables and sensor distributors are available. Additional product variants of the sensor, and further information and technical data can be found in the catalog chapter sensor system.

## APS-Z80 analog position sensor




No-contact measuring, analog multi-position monitoring for any number of positions.

Description	ID	Often combined
<b>Mounting kit for APS-Z80</b>		
AS-APS-Z80-PGZN-plus 160-1/200-2/240-2	0302113	
AS-APS-Z80-PGZN-plus 240-1	0302116	
<b>Analog position sensor</b>		
APS-Z80-K	0302072	
APS-Z80-M8	0302070	●

- ① When using an APS system, one mounting kit (AS-APS-Z80) and one APS-Z80 sensor is required per gripper. The resolution of the sensor can be lower in the peripheral areas of the gripper. You can find further information on the product in the operating manual.

APS-M1 analog position sensor




- 90 APS-M1S sensor
- 91 APS-M1E electronic processor
- 92 APS-K extension cable

Analog multi position monitoring for any desired positions

Description	ID	
Mounting kit for APS-M1		
AS-APS-M1-PGZN-plus 160-1/240-2	0302083	
AS-APS-M1-PGZN-plus 240-1	0302087	
Analog position sensor		
APS-M1S	0302062	
Connection cables		
APS-K0200	0302066	
APS-K0700	0302068	
Evaluation electronics		
APS-M1E	0302064	

- ① When using an APS system, for each gripper an attachment kit (AS-APS-M1), an APS-M1S sensor (incl. 3 m cable) as well as an electronics (APS-M1e) are required. An extension cable (APS-K) can be connected between the sensor and the electronics as an option. The max. cable length between the sensor and the electronics is 10 m, between the electronics and their control unit (PLC) it is max. 1 m.

Cylindrical reed switches



End position monitoring can be mounted with an attachment kit.

Description	ID	
Attachment kit for proximity switch		
AS-RMS 80 PGN/PZN-plus 160-380	0377727	
Reed Switches		
RMS 80-S-M8	0377721	

- ① Two sensors (closer/S) are required for each unit and extension cables are available as an option. This attachment kit needs to be ordered optionally as an accessory. Two mounting kits are required for each gripper. For sensor cables, note the minimum permissible bending radii. These are generally 35 mm.





**SCHUNK GmbH & Co. KG**  
**Spann- und Greiftechnik**

Bahnhofstr. 106 - 134  
D-74348 Lauffen/Neckar  
Tel. +49-7133-103-0  
Fax +49-7133-103-2399  
[info@de.schunk.com](mailto:info@de.schunk.com)  
[schunk.com](http://schunk.com)

Folgen Sie uns | *Follow us*

